Movelite WireFree 35 RTS

Based on DOC161449				
Date	Index	Page		
#DEE!	_ T	1/1		

Application scope









PINCH PLEAT

Main functionalities

- Manual operation in case of power failure
- Automatic end limits

- Touch motion
- Adjustable end limits

- "My" position
- Powered with rechargeable battery

Technical features

Power supply	Rechargeable 14.8V Li-ion battery pack
Standard by power consumption	<0.003W
Insulation class	Class III
Index protection rating	IP 20 - For indoor use only
Limit switch accuracy	±10
Touch motion sensitivity	4cm/8cm
Operating time	5 min
Maximum running time in one direction	2 min 30s

Temperature working range	0°C - 60°C	
Temperature charging range	0°C - 40°C	
Temperature storage range	-20°C - 60°C	
Compatible battery pack	LI-ION (2) BATTERY-4 ,	
Battery Charger	type C, G, A, I	

Specifications

Performance	
Nominal torque	0.6 Nm
Stall torque	0.8 Nm
Rated power	35 W
Maximum load	35 kg
Maximum track length	6 m
Minimum track length	0.6 m
Minimum bending radius	300 mm
Speed	105rpm
Linier speed	15cm/s
Mode option	NA
Noice level (Power)	41 dBA
Noice level (Pressure)	38 dBA
Lifetime	

Approvals





Radio

Radio protocol	RTS
Radio frequency	433MHz
Radio range	200 m in free field
Antenna	Integrated
Memory capacity	Maximum 12 RTS transmitters

Dimensions & Weight

L1	298 mm
L2	278 mm
L3	93 mm
L4	53 mm
Weight	1035 g





Limitations

For interior use only.

Motor must be installed vertically

Maximum distance between motor and charger: 4.5m

 $\label{lem:composition} Do \ not \ let \ the \ charger \ plugged \ in \ permanently \ to \ the \ motor. \ Somfy \ recommends \ to \ unplug \ after \ recharge.$



