# Sonesse® ULTRA 30 WireFree™ RTS Li-ion





# Lithium-ion +

#### **Built-in battery motor:**

- + All-in-one solution
- + Aesthetic
- + Compact & light
- + Battery power indicator
- + Easy recharging

The **Sonesse® ULTRA 30 WireFree™ Li-ion** is the quietest wire free motor dedicated to a wide range of interior applications. It features a rechargeable built in Li-Ion battery, a powerful lifting capacity and it is capable of precising tilting of blind slats.

# Compatible end-products







Roman blinds



Pleated and cellular blinds\*



Zebra blind



Sheer horizontal shades



Venetian blinds

\*Using CTS40

# Main functionalities



For large size blinds Capable of lifting up to 18 m2 blinds (2 Nm)



# Designed for silence





#### Built-in battery motor Powered by a compact & light lithium-ion battery, for a better integration.



#### Thin head White and thin round head for discreet blending



Soft start and Soft stop



Information feedback low battery indicator on the controller interface and easy re-setting.



Adjustable speed From 10 to 28 rpm.



Compatible with modulis functions



Slats tilting

# Benefits for professionals

#### Convenience

 Can motorize a wide range of roller and venetian blinds

# **Easy installation**

- No wires nor external batteries
- Sleep mode to prevent the motor from unwanted pairing

#### Easy re-setting

- Programming button and LED on motor head interface
- Up and down end limits set via transmitter

#### Reliability and profitability

- Safe protocol
- Somfy quality & warranty
- So Open with Somfy

# Benefits for end-users

#### **Daily comfort**

- Quiet operation
- Smooth motion with adjustable speed
- Tilting precision

#### **Aesthetic integration**

Discreet design, no wires nor external batteries

#### Easy use and maintenance

- Rechargeable battery
- Low battery LED indicator on motor head interface

- No electrical wires nor cords, free from danger of strangling
- Somfy quality and warranty





# Sonesse® ULTRA 30 WireFree™ RTS Li-ion



# **Technical features**

Voltage Supply 12V DC

Index Protecting

rating

IP 20 (for indoor use only)

Limit Switch type

Electronic

Temperature working range

0°C to 60°C

Temperature storage range

-20°C to 60°C

Insulation class

Class III

**Antenna** 

15 cm wire length, must not be cut or lengthened. For greatest RF range, must not be exposed and should not come in contact with metal surfaces. RF wire may need to be repositioned for optimal

performance.

# **Dimensions**

Motor length ~635 mm

Head length ~9 mm

Tube min Ø (int): 28,8 mm



# **Performances**

Nominal torque	2 Nm
Nominal Speed	20 rpm
Adjustable speed	10-28 by increment of 2 rpm
Sound level	99999
Radio Protocol	RTS
Radio Frequency	433.42 MHz
Battery type	12V 2600 mAh (built-in Lithium-Ion)
Battery autonomy	Only recharge once per year*
Charging time	< 4,5 hours
Low Battery Indicator	LED

<sup>\*</sup> With one cycle (up and down) per day. For optimal performance, please refer to Abacus.

# Certifications














# Sonesse® 30 WireFree™ RTS Li-ion





# **W**ireFree™

# Lithium-ion +

#### **Built-in battery motor:**

- + All-in-one solution
- + Aesthetic
- + Compact & light
- + Battery power indicator
- + Easy recharging

The **Sonesse® 30 WireFree™ Li-ion** is a quiet wire free motor dedicated to a wide range of interior applications. It features a rechargeable built in Li-Ion battery, a powerful lifting capacity and it is capable of precising tilting of blind slats.

# Compatible end-products













Pleated and cellular blinds\*

Zebra blind Sheer horizo shades

Venetian blinds


\*Using CTS40

#### Main functionalities



For large size blinds Capable of lifting up to 18 m2 blinds (2 Nm)





888



Built-in battery motor Powered by a compact & light lithium-ion battery, for a better integration.



Thin head White and thin round head for discreet blending



Soft start and Soft stop



Information feedback low battery indicator on the controller interface and easy re-setting.



Adjustable speed From 10 to 28 rpm.



Compatible with modulis functions



**Slats tilting** 

# Benefits for professionals

#### Convenience

Can motorize a wide range of roller and venetian blinds

# **Easy installation**

- No wires nor external batteries
- Sleep mode to prevent the motor from unwanted pairing

#### Easy re-setting

- Programming button and LED on motor head interface
- Up and down end limits set via transmitter

# Reliability and profitability

- Safe protocol
- Somfy quality & warranty
- So Open with Somfy

# Benefits for end-users

# Daily comfort

- Quiet operation
- Smooth motion with adjustable speed
- Tilting precision

#### **Aesthetic integration**

Discreet design, no wires nor external batteries

# Easy use and maintenance

- Rechargeable battery
- Low battery LED indicator on motor head interface

- No electrical wires nor cords, free from danger of strangling
- Somfy quality and warranty





# Sonesse® 30 WireFree™ RTS Li-ion







# **Technical features**

Voltage Supply 12V DC

**Index Protecting** 

IP 30 (for indoor use only)

rating

Limit Switch type Electronic

Temperature working range

0°C to 60°C

Temperature storage range

-20°C to 60°C

Insulation class

Class III

**Antenna** 

17,5 cm wire length, must not be cut or lengthened. For greatest RF range, must not be exposed and should not come in contact with metal surfaces. RF wire may need to be repositioned for optimal

performance.

# **Dimensions**

Motor length ~595 mm

**Head length** ~7,5 mm

Tube min Ø (int): 28,8 mm



# **Performances**

Nominal torque	2 Nm
Nominal Speed	20 rpm
Adjustable speed	10-28 by increment of 2 rpm
Sound level	999
Radio Protocol	RTS
Radio Frequency	433.42 MHz
Battery type	12V 2600 mAh (built-in Lithium-Ion)
Battery autonomy	Only recharge once per year*
Charging time	< 4,5 hours
Low Battery Indicator	LED

<sup>\*</sup> With one cycle (up and down) per day. For optimal performance, please refer to Abacus.

# Certifications















# Sonesse® 28 WireFree™ RTS Li-ion







# Lithium-ion +

#### **Built-in battery motor:**

- + All-in-one solution
- + Aesthetic
- + Compact & light
- + Battery power indicator
- + Easy recharging

The **Sonesse® 28 WireFree™ RTS Li-ion** is a easy-to-fit wire free motor, surprisingly quiet. It features a rechargeable built in Li-ion battery for a easier maintenance and a sleek design.

# Compatible end-products









Pleated and cellular blinds\*



Zebra blind



Sheer horizontal shades

\*Using CTS40

# Main functionalities



# For medium size blinds

Capable of lifting up to 12 m2 blinds (1,1 Nm)



Designed for silence





#### Built-in battery motor

Powered by a compact & light lithium-ion battery, for a better integration.



#### Thin head

White and thin round head for discreet blending



Soft start and Soft stop



Information feedback low battery indicator on the controller interface and easy re-setting.



Adjustable speed From 10 to 28 rpm.



Compatible with modulis functions

# Benefits for professionals

#### Convenience

• Can motorize a wide range of roller blinds **Easy installation** 

- No wires nor external batteries
- Sleep mode to prevent the motor from unwanted pairing

#### Easy re-setting

- Programming button and LED on motor head interface
- Up and down end limits set via transmitter

#### Reliability and profitability

- Safe protocol
- Somfy quality & warranty
- So Open with Somfy

# Benefits for end-users

# **Daily comfort**

- Quiet operation
- Smooth motion with adjustable speed

#### **Aesthetic integration**

 Discreet design, no wires nor external batteries

#### Easy use and maintenance

- Rechargeable battery
- Low battery LED indicator on motor head interface

- No electrical wires nor cords, free from danger of strangling
- Somfy quality and warranty





# Sonesse® 28 WireFree™ RTS Li-ion



# **Technical features**

Voltage Supply 12V DC

Index Protecting IP 20 (for indoor use only)

rating

Limit Switch type Electronic

Temperature working range

0°C to 60°C

Temperature storage range

-20°C to 60°C

Insulation class III

Antenna 15 cm wire length, must not be cut

or lengthened. For greatest RF range, must not be exposed and should not come in contact with metal surfaces. RF wire may need to be repositioned for optimal

performance.


# **Dimensions**

Ongoing project, specifications might slightly change

Motor length ~530 mm

**Head length** ~9 mm

Tube min Ø (int): 26,6 mm



# **Performances**

Ongoing project, specifications might slightly change

Nominal torque	1,1 Nm
Nominal Speed	28 rpm
Adjustable speed	10-28 by increment of 2 rpm
Sound level	999
Radio Protocol	RTS
Radio Frequency	433.42 MHz
Battery type	12V 2600 mAh (built-in Lithium-Ion)
Battery autonomy	Only recharge once per year*
Recharging time	< 4,5 hours
Low Battery Indicator	LED

<sup>\*</sup> With one cycle (up and down) per day. For optimal performance, please refer to Abacus.

# Certifications















# Roll Up 24 WireFree™ RTS Li-ion





# Lithium-ion 4

#### Built-in battery motor:

The Roll Up 24 WireFree™ RTS Li-ion is the smallest wire free motor, that fits the smallest tubes of Ø24 mm. It features a rechargeable built in Li-ion battery for a easier maintenance and a sleek design.

# Compatible end-products







Roller blinds

Roman blinds

Main functionalities



# For small size blinds

Capable of lifting up to 5 m2 blinds (0,5 Nm)



# Built-in battery motor

Powered by a compact & light lithium-ion battery, for a better integration.



#### Thin head

White and thin round head for discreet blending SOFT START AND SOFT STOP Soft start and Soft stop



#### Information feedback

low battery indicator on the controller interface and easy re-setting.



# Adjustable speed

From 20 to 38 rpm.



#### Compatible with modulis functions

# Benefits for professionals

#### **Easy installation**

- No wires nor external batteries
- Sleep mode to prevent the motor from unwanted pairing

#### Easy re-setting

- Programming button and LED on motor head
- Up and down end limits set via transmitter

#### Reliability and profitability

- Safe protocol
- Somfy quality & warranty
- So Open with Somfy

# Benefits for end-users

#### **Daily comfort**

- Smooth motion with adjustable speed
- **Aesthetic integration**
- Discreet design, no wires nor external batteries

#### Easy use and maintenance

- Rechargeable battery
- Low battery LED indicator on motor head interface

- No electrical wires nor cords, free from danger of strangling
- Somfy quality and warranty





- + All-in-one solution
- + Aesthetic
- + Compact & light
- + Battery power indicator
- + Easy recharging

# Roll Up 24 WireFree™ RTS Li-ion



# **Technical features**

Voltage Supply 12V DC

Index Protecting IP 20 (for indoor use only)

rating

Limit Switch type Electronic

Temperature working range

0°C to 60°C

Temperature storage range

-20°C to 60°C

Insulation class

Class III

Antenna

15 cm wire length, must not be cut or lengthened. For greatest RF range, must not be exposed and should not come in contact with metal surfaces. RF wire may need to be repositioned for optimal

performance.


# **Dimensions**

Ongoing project, specifications might slightly change

Motor length ~478 mm

**Head length** ~9 mm

Tube min Ø (int): 23,8 mm



# **Performances**

Ongoing project, specifications might slightly change

Nominal torque	0,55 Nm
Nominal Speed	38 rpm
Adjustable speed	20-38 by increment of 2 rpm
Sound level	Not Designed for Silence
Radio Protocol	RTS
Radio Frequency	433.42 MHz
Battery type	12V 1400 mAh (built-in Lithium-Ion)
Battery autonomy	Recharge twice a year*
Recharging time	< 4 hours
Low Battery Indicator	LED

<sup>\*</sup> With one cycle (up and down) per day. For optimal performance, please refer to Abacus.

# **Certifications**







# Jr Roll Up 30 WireFree™ RTS Li-ion





# Lithium-ion +

#### **Built-in battery motor:**

- + All-in-one solution
- + Aesthetic
- + Compact & light
- + Battery power indicator
- + Easy recharging

The Jr Roll Up 30 RTS Li-ion embodies Somfy essentials making motorization accessible to all. Wire free, it features a rechargeable built in Li-ion battery for a easier maintenance and a sleek design.

# Compatible end-products





Roller blinds

Roman blinds

# Main functionalities



# For small size blinds

Capable of lifting up to 3,5 m2 blinds (0,35 Nm)



# Built-in battery motor

Powered by a compact & light lithium-ion battery, for a better integration.



#### Thin head

White and thin round head for discreet blending



Soft start and Soft stop



#### Information feedback

low battery indicator on the controller interface and easy re-setting.

# Benefits for professionals

#### Affordable solution **Easy installation**

- No wires nor external batteries
- Sleep mode to prevent the motor from unwanted pairing

#### Easy re-setting

- Programming button and LED on motor head
- Up and down end limits set via transmitter

# Reliability and profitability

- Safe protocol
- Somfy quality & warranty
- So Open with Somfy

# Benefits for end-users

# Affordable solution

#### **Aesthetic integration**

Discreet design, no wires nor external batteries

#### Easy use and maintenance

- Rechargeable battery
- Low battery LED indicator on motor head interface

- No electrical wires nor cords, free from danger of strangling
- Somfy quality and warranty



# Jr Roll Up 30 WireFree™ RTS Li-ion



# **Technical features**

Voltage Supply 12V DC

Index Protecting IP 30 (for indoor use only)

rating

Limit Switch type Electronic

Temperature working range

0°C to 60°C

Temperature storage range

-20°C to 60°C

Insulation class III

Antenna 15 cm wire length, must not be cut

or lengthened. For greatest RF range, must not be exposed and should not come in contact with metal surfaces. RF wire may need to be repositioned for optimal


performance.

# **Dimensions**

Motor length ~417 mm

**Head length** ~9 mm

Tube min Ø (int): 26,6 mm



# **Performances**

Nominal torque	0,35 Nm
Nominal Speed	40 rpm
Sound level	Not Designed for Silence
Radio Protocol	RTS
Radio Frequency	433.42 MHz
Battery type	12V 2600 mAh (built-in Lithium-Ion)
Battery autonomy	Only recharge once per year*
Recharging time	< 4,5 hours
Low Battery Indicator	LED

<sup>\*</sup> With one cycle (up and down) per day. For optimal performance, please refer to Abacus.

# **Certifications**









# Roll Up 28 WireFree™ RTS





The **Altus 28 WireFree™ RTS** is a compact wire free motor for a wide range of roller blinds.

It is powered by an external Lithium-ion battery pack for an easier maintenance.

# Compatible end-products



Roller blinds









Roman blinds Pleated and cellular blinds\*

Zebra blind Sheer horizontal shades

# Main functionalities



# For medium size blinds

Capable of lifting 6 m<sup>2</sup> blinds (1,5 Nm)



# Built-in battery motor

Powered by a compact & light Li-ion battery, for a better integration.



#### Thin head

White and thin round head for discreet blending

SOFT START AND SOFT STOP

Soft start and Soft stop



#### Information feedback

low battery indicator on the controller interface and easy re-setting.



#### Adjustable speed

From 10 to 28 rpm.



# Compatible with modulis functions

# Benefits for professionals

#### Convenience

- Can motorize a wide range of roller blinds
- A compact solution for the smallest applications

# **Easy installation**

Sleep mode to prevent the motor from unwanted pairing

#### Easy re-setting

- Programming button and LED on motor head interface
- Up and down end limits set via transmitter

#### Reliability and profitability

- Safe protocol
- Somfy quality & warranty
- So Open with Somfy

# Benefits for end-users

#### **Daily comfort**

Smooth motion with adjustable speed

#### Easy use and maintenance

- Compatible with external rechargeable battery packs
- Low battery LED indicator on motor head interface

- No electrical wires nor cords, free from danger of strangling
- Somfy quality and warranty





<sup>\*</sup>Using CTS40

# Roll Up 28 WireFree™ RTS



# **Technical features**

Voltage Supply 12V DC

Index Protecting

rating

IP 20 (for indoor use only)

Limit Switch type Electronic

Temperature working range

0°C to 50°C

Temperature storage range

-10°C to 60°C

Insulation class

Class III

**Antenna** 

17,5 cm wire length, must not be cut or lengthened. For greatest RF range, must not be exposed and should not come in contact with metal surfaces. RF wire may need to be repositioned for optimal


performance.

# **Dimensions**

Motor length ~355 mm

Motor head ~7,5mm

Tube min Ø (int): 26,6 mm



# **Performances**

Nominal Torque	1,1 Nm
Nominal Speed	28 rpm
Adjustable Speed	10-28 by increment of 2 rpm
Sound Level	Not Designed for Silence
Radio Protocol	RTS
Radio Frequency	433.42 MHz
Power Supply	External primary* or rechargeable battery**
Low Battery Indicator	LED

<sup>\*</sup> Alcaline, Ni-MH, Lithium battery tube

# Certifications









<sup>\*\*</sup> Li-ion battery pack (2600 mAh)

# Roll Up Basic 28 WireFree™ RTS Li-ion





# Lithium-ion +

#### **Built-in battery motor:**

- + All-in-one solution
- + Aesthetic
- + Compact & light
- + Battery power indicator
- + Easy recharging

The **Altus Basic 28 WireFree™ RTS Li-ion** embodies Somfy essentials, at an affordable price. It features a rechargeable built in Li-ion battery for a easier installation, maintenance and improved aesthetics.

# Compatible end-products







Roller blinds

Roman blinds

Main functionalities



#### For small size blinds Capable of lifting 4 m<sup>2</sup> blinds (0,7 Nm)



Built-in battery motor Powered by a compact { light Li-ion battery, for better integration.



Thin head White and thin round head for discreet blending



Soft start and Soft stop



#### Information feedback low battery indicator on the controller interface and easy re-setting.



Compatible with modulis functions

# Benefits for professionals

#### **Easy installation**

- No wires nor external batteries
- Sleep mode to prevent the motor from unwanted pairing

# Easy re-setting

- Programming button and LED on motor head interface
- Up and down end limits set via transmitter

# Reliability and profitability

- Safe protocol
- Somfy quality & warranty
- So Open with Somfy

# Benefits for end-users

# **Aesthetic integration**

 Discreet design, no wires nor external batteries

#### Easy use and maintenance

- Rechargeable battery
- Low battery LED indicator on motor head interface

- No electrical wires nor cords, free from danger of strangling
- Somfy quality and warranty





# Roll Up Basic 28 WireFree™ RTS Li-ion





# **Technical features**

Voltage Supply 12V DC

Index Protecting

IP 20 (for indoor use only)

rating

Limit Switch type Electronic

Temperature working range

0°C to 50°C

Temperature storage range

-10°C to 60°C

Insulation class

Class III

**Antenna** 

17,5 cm wire length, must not be cut or lengthened. For greatest RF range, must not be exposed and should not come in contact with metal surfaces. RF wire may need to be repositioned for optimal


performance.

# **Dimensions**

Motor length ~580 mm

Motor head ~7,5mm

Tube min Ø (int): 26,6 mm



# **Performances**

Nominal Torque	0,7 Nm
Nominal Speed	28 rpm
Sound Level	Not Designed for Silence
Radio Protocol	RTS
Radio Frequency	433.42 MHz
Battery type	12V 1400 mAh (built-in Lithium-Ion)
Battery Autonomy	Recharge twice per year*
Recharging time	< 4,5 hours
Low Battery Indicator	LED

<sup>\*</sup> With one cycle (up and down) per day. For optimal performance, please refer to Abacus.

# **Certifications**







# Tilt Only 50 WireFree™ RTS Central







The **Tilt Only 50 WireFree™ RTS central** is a through- shaft motor, specifically designed for tilting wooden venetian blinds.

# Compatible end-products





Venetian blinds

Wood & faux wood venetian blinds

# Main functionalities



#### Battery operated motor Powered with primary

Powered with primary batteries, batteries, solar pack or power supply



#### Soft start and Soft stop



# Adjustable speed From 5 to 15 rpm.



Compatible with modulis functions



Slats tilting



# **Central position**

For a wider applications scope (namely venetian recut)

# Benefits for professionals

# **Easy integration**

- Suitable to headrails of at least 50 mm width
- Through-shaft motor for a central position in the headrail

#### **Easy installation**

No wires

# Reliability and profitability

- Safe protocol
- Somfy quality & warranty
- So Open with Somfy

# Benefits for end-users

#### **Daily comfort**

- Smooth motion with adjustable speed
- Tilting precision

#### **Discreet integration**

No damage to walls

#### **Energy savings**

Low consumption motor

- No electrical wires nor cords, free from danger of strangling
- Somfy quality and warranty





# Tilt Only 50 WireFree™ RTS Central



# **Technical features**

Voltage Supply 12V DC

**Index Protecting** 

rating

IP 30 (for indoor use only)

Limit Switch type

Electronic

Temperature working range

0°C to 60°C

Temperature storage range

-20°C to 60°C

Insulation class

Class III

**Antenna** 


15 cm wire length, must not be cut or lengthened. For greatest RF range, must not be exposed and should not come in contact with metal surfaces. RF wire may need to be repositioned for optimal

performance.

# **Dimensions**

Ongoing project, specifications might slightly change

Length (L) >100 mm



# **Performances**

Ongoing project, specifications might slightly change

3 31 7 7 1	<del>, , , , , , , , , , , , , , , , , , , </del>
Nominal torque	1 Nm
Nominal Speed	10 rpm
Adjustable speed	5-15 rpm by increment of 1 rpm
Sound level	Not Designed for Silence
Radio Protocol	RTS
Radio Frequency	433.42 MHz
Power Supply	External primary* or rechargeable battery**

<sup>\*</sup> Alcaline, Ni-MH, Lithium battery tube

# **Certifications**







<sup>\*\*</sup> Li-ion battery pack (2600 mAh)

# Tilt & Lift 25 WireFree™ RTS Central





The **Tilt & Lift 25 WireFree™ RTS central** is a double output motor, specifically designed for tilting small venetian blinds.

# Compatible end-products







Roman blinds

Pleated and cellular blinds\*

Venetian blinds

#### Main functionalities



Designed for silence



Battery operated motor

Powered with primary batteries, batteries, solar pack or power supply



Soft start and Soft stop



Adjustable speed From 15 to 30 rpm



Compatible with modulis functions



Tilt & Lift
Can both tilt and
lift venetian blinds



Central position

For a wider applications scope (namely venetian recut)

# Benefits for professionals

# **Easy integration**

- Suitable to headrails of at least 25 x 25 mm
- Double output motor for a central position in the headrail

# **Easy installation**

No wires

# Reliability and profitability

- Safe protocol
- Somfy quality & warranty
- So Open with Somfy

# Benefits for end-users

#### **Daily comfort**

- Re-designed for a quieter performance
- Smooth motion with adjustable speed
- Tilt & Lift function

#### **Discreet integration**

No damage to walls

- No electrical wires nor cords, free from danger of strangling
- Somfy quality and warranty

# Tilt & Lift 25 WireFree™ RTS Central



# **Technical features**

Voltage Supply 12V DC

Index Protecting IP 30

rating

IP 30 (for indoor use only)

Limit Switch type Electronic

Temperature working range

0°C to 60°C

Temperature storage range

-20°C to 60°C

Insulation class III

Antenna 15 cm wire length, must not be cut


or lengthened. For greatest RF range, must not be exposed and should not come in contact with metal surfaces. RF wire may need to be repositioned for optimal

performance.

# **Dimensions**

Ongoing project, specifications might slightly change

Length (L1) ~200 mm



# **Performances**

Ongoing project, specifications might slightly change

Nominal torque	0,8 Nm
Nominal Speed	30 rpm
Adjustable speed	15-30 rpm by increment of 1 rpm
Sound level	999
Radio Protocol	RTS
Radio Frequency	433.42 MHz
Power Supply	External primary* or rechargeable battery**

<sup>\*</sup> Alcaline, Ni-MH, Lithium battery tube

# **Certifications**







<sup>\*\*</sup> Li-ion battery pack (2600 mAh)